



IBIX®

SPECIAL CLEANING

IBIX® 9 H₂O

IBIX® H₂O offers two different operating modes: dry or with a nebulized low-pressure water jet mixed with the abrasive; the mix happens in the nozzle so that the quantity of water used is reduced, along with the cleaning residues and the cost of protecting nearby areas.

The use of water prevents dust to spread in the surroundings and is perfect in urban contexts or where it is particularly important to reduce emissions.

IBIX® 9 H₂O

TECHNICAL FEATURES

- Pressure adjustable from 0.2 to 7.5* bar
- Micrometric dosing of the blasting material
- Particles can range in size from 38 µm up to 600 µm and have different specific gravity (from Natural Mineral Almandine to Sodium Bicarbonate, Calcium Carbonate, Magnesium Carbonate, glass beads and vegetal media)
- Recommended compressed air supply: 500 l/min (17.6 CFM)
- Standard nozzle: internal Ø 3 mm cylindrical
- Other applicable nozzles: internal Ø 1.5-2-2.5-3 L. 115-3.5-4-4.5 mm cylindrical and 2.5-4-4 L. 115 mm Venturi
- Blasting medium - air hose with protective sheath: 6 m
- Blasting medium tank capacity: 9 l
- Max height: 715 mm
- Max width: 325 mm
- Max length: 350 mm
- Weight (with empty tank): 18 kg approx.

*Depending on the compressor



A 90 (MOTOR-DRIVEN COMPRESSOR)



TECHNICAL FEATURES

- Wheeled air compressor with high capacity Cejn type fittings
- Engine power: HONDA ENGINE 9 Hp
- Air flow rate: 500 l/min (17.6 CFM)
- Max. pressure: 10 bar (150 psi)
- Noise Level: 77 dB(A)
- Weight: 108 kg (235 lb)
- Dimensions: 1070x770x890 mm (42x30x35 in)

The A 90 Motor-driven compressor is equipped with connections suitable to match with the IBIX® 9 System concerning dimensions and air flow.

ELECTRIC AIR DRYER T-DRY 6 FOR A 90 COMPRESSOR



TECHNICAL FEATURES

- Air drying capacity: 600 l/m
- Volt/Hz: 230/60/1
- Max. Watt: 260
- Dimensions: 370x515x475 mm
- Weight: 25 kgs

Complete with hose and fittings for quick coupling to the A 90 compressor or equivalent.

24 L STAINLESS STEEL SPRAYER

TECHNICAL FEATURES

- 24 l (5.28 gal) stainless steel tank wheeled
- Max working pressure: 8 bar (116 psi)
- Empty weight: 15 kg (33 lb)
- Compressed air connector
- Water spray nozzle with special support bracket for IBIX® spray gun fixing, water on/off tap, tank to nozzle water delivery hose
- Nozzle model LM/75 with 7.5 m RILSAN spiral pipe

Dust removal by finely sprayed water dome, especially useful in case of very fine grain sized blasting materials



NOZZLE BOX IBIX® 9 H₂O

Nozzle :

- 2 - 4 mm cylindrical
- 2,5 - 4 mm Venturi

